

AERONAUTICAL DATA TABULATION

RNAV(GNSS) RWY12

Serial number	Path descriptor	Fix identifier	Flyover	Course °M(°T)	Dist,km	Turn direction	Altitude,m	Speed, (km/h)	Coordinates	VPA/RDH	Navigation specification	Remarks
1	IF	CD103	-	-	-	-	+1500	-	48 12 13.28N 114 23 49.45E	-	RNP APCH	IF
2	TF	CD104	-	121(112.2)	8.5	-	@1300	-	48 10 29.25N 114 30 10.47E	-	RNP APCH	FAF
3	TF	RWY12	Y	121(112.2)	10.25	-	+950	-	48 08 23.85N 114 37 49.68E	-3.0/15	RNP APCH	MAPT
4	FA	-	-	121(112.2)	-	-	+1000	-	-	-	RNP APCH	-
5	DF	CD103	Y	-	-	R	-	-	48 12 13.28N 114 23 49.45E	-	RNP APCH	MAHF

HOLDING PROCEDURE

Holding Identification	Path descriptor	Fix identifier	Inbound course °M(°T)	Leg distance (min)	Turn direction	Minimum altitude	Speed limit, (km/h)	Coordinates	Magnetic variation	Navigation specification
RNAV (GNSS)RWY 12	HM	CD103	121(112.2)	1min	L	+1500	-	48 12 13.28N 114 23 49.45E	8 W	RNP APCH

M/FT CONVERSION

ELEVATION	
m	ft
748	2454
766	2513
775	2543
800	2625
815	2674
827	2713
836	2743
846	2776
865	2838
1020	3346
1034	3392

ALTITUDE	
m	ft
860	2830
900	2960
950	3120
960	3150
1000	3290
1055	3470
1155	3790
1250	4110
1300	4270
1500	4930
1800	5910
2100	6890
8000	26250

LEVEL	
m	ft
2400	7900