

AERONAUTICAL DATA TABULATION

RNAV(GNSS) RWY30

Serial number	Path descriptor	Fix identifier	Flyover	Course °M(°T)	Dist,km	Turn direction	Altitude,m	Speed, (km/h)	Coordinates	VPA/RDH	Navigation specification	Remarks
1	IF	CD302	-	-	-	-	+1500	-	48 08 45.50N 114 56 42.46E	-	RNP APCH	IAF
2	TF	CD303	-	211(202.2)	9.50	-	+1300	-	48 04 00.82N 114 53 48.59E	-	RNP APCH	IF

Serial number	Path descriptor	Fix identifier	Flyover	Course °M(°T)	Dist,km	Turn direction	Altitude,m	Speed, (km/h)	Coordinates	VPA/RDH	Navigation performance	Remarks
1	IF	CD301	-	-	-	-	+1500	-	47 59 16.07N 114 50 55.25E	-	RNP APCH	IAF
2	TF	CD303	-	029(020.2)	9.50	-	+1300	-	48 04 00.82N 114 53 48.59E	-	RNP APCH	IF
3	TF	CD304	-	301(292.2)	8.40	-	@1300	-	48 05 43.88N 114 47 33.00E	-	RNP APCH	FAF
4	TF	RWY30	Y	301(292.2)	10.44	-	+900	-	48 07 52.02N 114 39 45.94E	-3.0/15	RNP APCH	MAPT
5	FA	-	-	301(292.2)	-	-	+1000	-	-	-	RNP APCH	-
6	DF	CD302	Y	-	-	R	-	-	48 08 45.50N 114 56 42.46E	-	RNP APCH	MAHF

HOLDING PROCEDURE

Holding Identification	Path descriptor	Fix identifier	Inbound course °M(°T)	Leg distance (min)	Turn direction	Minimum altitude	Speed limit, (km/h)	Coordinates	Magnetic variation	Navigation specification
RNAV (GNSS)RWY 30	HM	CD302	211(202.2)	1min	L	+1500	-	48 08 45.50N 114 56 42.46E	8 W	RNP APCH

M/FT CONVERSION

ELEVATION	
m	ft
738	2421
748	2454
766	2513
775	2543
792	2598
807	2648
808	2651
809	2654
815	2674
846	2776
865	2838

ALTITUDE	
m	ft
850	2790
855	2810
900	2960
950	3120
1000	3290
1045	3430
1140	3750
1240	4070
1300	4270
1500	4930
1800	5910
2100	6890
8000	26250

LEVEL	
m	ft
2400	7900