

AERONAUTICAL DATA TABULATION

RNP RWY34

Serial number	Path descriptor	Fix identifier	Flyover	Course °M(°T)	Dist,km	Turn direction	Altitude,m	Speed, (km/h)	Coordinates	VPA/RDH	Navigation specification	Remarks
1	IF	KD101	–	–	–	–	+3300	–	47 46 21.30N 091 57 04.70E	–	RNP APCH	IAF
2	TF	KD102	–	235(237.4)	9.26	–	+2800	–	47 43 39.73N 091 50 50.04E	–	RNP APCH	IF
3	TF	KD103	–	305(307.4)	11.11	–	@2600	–	47 47 18.29N 091 43 46.21E	–	RNP APCH	FAF
4	TF	KD34M	Y	335(337.4)	16.67	–	+1750	–	47 55 36.54N 091 38 38.11E	3.4	RNP APCH	MAPT
5	DF	KD104	–	335(337.4)	23.22	R	–	-345	48 07 10.42N 091 31 26.54E	–	RNP APCH	MATF
6	TF	KD105	–	065(067.4)	9.26	R	–	-345	48 09 05.51N 091 38 20.11E	–	RNP APCH	MATF
7	TF	KD106	–	146(148.3)	23.49	–	+3000	-345	47 58 17.71N 091 48 15.00E	–	RNP APCH	MATF
8	HM	KD106	–	151(153.5)	1min	L	+3000	-425	47 58 17.71N 091 48 15.00E	–	RNP APCH	MAHF

HOLDING PROCEDURE

Holding Identification	Path descriptor	Fix identifier	Inbound course °M(°T)	Leg distance (min)	Turn direction	Minimum altitude	Speed limit, (km/h)	Coordinates	VPA/RDH	Navigation specification
RNAV (GNSS)RWY 34	HM	KD101	235(237.4)	1min	R	3300	-425	47 46 21.30N 091 57 04.70E	–	RNP APCH

M/FT CONVERSION

ELEVATION			
m	ft	m	ft
1493	4898	2008	6588
1554	5098	2026	6647
1587	5207	2027	6650
1606	5269	2042	6699
1609	5279	2048	6719
1611	5285	2061	6762
1656	5433	2062	6765
1700	5577	2102	6896
1788	5866	2108	6916
1802	5912	2114	6936
1822	5978	2132	6995
1846	6056	2161	7090
1875	6152	2162	7093
1885	6184	2167	7109
1886	6188	2248	7375
1889	6197	2260	7415
1935	6348	2300	7546
1941	6368	2379	7805
2000	6562	2600	8530
2001	6565	2843	9327
2006	6581	2900	9514

ALTITUDE	
m	ft
1730	5680
1735	5700
1750	5750
1890	6210
1900	6240
1950	6400
2160	7090
2175	7140
2400	7880
2500	8210
2560	8400
2600	8540
2800	9190
3000	9850
3200	10500
3300	10830
3600	11820
3900	12800
4500	14770
7300	23950

LEVEL	
m	ft
4200	13800