

INSTRUMENT
APPROACH
CHART-ICAO

DORNOD/Choibalsan (ZMCD)
RNP RWY 12 (LNAV only)
ACFT CAT A/B, C

AERONAUTICAL DATA TABULATION

RNP RWY12 (LNAV only)

Serial number	Path descriptor	Fix identifier	Flyover	Course °M(°T)	Dist,km	Turn direction	Altitude,m	Speed, (km/h)	Coordinates	VPA/RDH	Navigation specification	Remarks
1	IF	CD103	-	-	-	-	+1500	-	48 12 13.28N 114 23 49.45E	-	RNP APCH	IF
2	TF	CD104	-	121(112.2)	8.5	-	@1300	-	48 10 29.25N 114 30 10.47E	-	RNP APCH	FAF
3	TF	RWY12	Y	121(112.2)	10.25	-	+950	-	48 08 23.85N 114 37 49.68E	-3.0/15	RNP APCH	MAPT
4	FA	-	-	121(112.2)	-	-	+1000	-	-	-	RNP APCH	-
5	DF	CD103	Y	-	-	R	-	-	48 12 13.28N 114 23 49.45E	-	RNP APCH	MAHF

HOLDING PROCEDURE

Holding Identification	Path descriptor	Fix identifier	Inbound course °M(°T)	Leg distance (min)	Turn direction	Minimum altitude	Speed limit, (km/h)	Coordinates	Magnetic variation	Navigation specification
RNP RWY 12 (LNAV only)	HM	CD103	121(112.2)	1min	L	+1500	-	48 12 13.28N 114 23 49.45E	9 W	RNP APCH

M/FT CONVERSION

ELEVATION	
m	ft
748	2454
754	2474
762	2500
766	2513
772	2533
783	2569
787	2582
788	2585
791	2595
798	2618
807	2648
808	2651
810	2657
828	2717
851	2792
896	2940
1020	3346
1033	3389

ALTITUDE	
m	ft
860	2830
900	2960
950	3120
960	3150
1000	3290
1055	3470
1155	3790
1250	4110
1300	4270
1500	4930
3900	12800
4200	13780
8000	26250

LEVEL	
m	ft
4500	14800