

INSTRUMENT
APPROACH
CHART-ICAO

DORNOD/Choibalsan (ZMCD)
RNP RWY 30 (LNAV only)
ACFT CAT A/B, C

AERONAUTICAL DATA TABULATION

RNP RWY30 (LNAV only)

Serial number	Path descriptor	Fix identifier	Flyover	Course °M(°T)	Dist,km	Turn direction	Altitude,m	Speed, (km/h)	Coordinates	VPA/RDH	Navigation specification	Remarks
1	IF	CD302	–	–	–	–	+1500	–	48 08 45.50N 114 56 42.46E	–	RNP APCH	IAF
2	TF	CD303	–	211(202.2)	9.50	–	+1300	–	48 04 00.82N 114 53 48.59E	–	RNP APCH	IF

Serial number	Path descriptor	Fix identifier	Flyover	Course °M(°T)	Dist,km	Turn direction	Altitude,m	Speed, (km/h)	Coordinates	VPA/RDH	Navigation performance	Remarks
1	IF	CD301	–	–	–	–	+1500	–	47 59 16.07N 114 50 55.25E	–	RNP APCH	IAF
2	TF	CD303	–	031(022.2)	9.50	–	+1300	–	48 04 00.82N 114 53 48.59E	–	RNP APCH	IF
3	TF	CD304	–	301(292.2)	8.40	–	@1300	–	48 05 43.88N 114 47 33.00E	–	RNP APCH	FAF
4	TF	RWY30	Y	301(292.2)	10.44	–	+900	–	48 07 52.02N 114 39 45.94E	-3.0/15	RNP APCH	MAPT
5	FA	–	–	301(292.2)	–	–	+1000	–	–	–	RNP APCH	–
6	DF	CD302	Y	–	–	R	–	–	48 08 45.50N 114 56 42.46E	–	RNP APCH	MAHF

HOLDING PROCEDURE

Holding Identification	Path descriptor	Fix identifier	Inbound course °M(°T)	Leg distance (min)	Turn direction	Minimum altitude	Speed limit, (km/h)	Coordinates	Magnetic variation	Navigation specification
RNP RWY 30 (LNAV only)	HM	CD302	211(202.2)	1min	L	+1500	–	48 08 45.50N 114 56 42.46E	9 W	RNP APCH

M/FT CONVERSION

ELEVATION	
m	ft
739	2425
745	2444
747	2451
748	2454
754	2474
762	2500
766	2513
772	2533
783	2569
787	2582
788	2585
791	2595
798	2618
807	2648
828	2717
836	2743
851	2792
852	2795
896	2940

ALTITUDE	
m	ft
850	2790
855	2810
900	2960
950	3120
1000	3290
1045	3430
1140	3750
1240	4070
1300	4270
1500	4930
3900	12800
4200	13780
8000	26250

LEVEL	
m	ft
4500	14800